technical specifications

Product Name Product Description

Pile Yarn Description

Roll Length
Roll Width
Total Weight
Total Thickness
Wear Classification
Flammability

Thermal Resistance Castor Chair Rating Static Loading

Dynamic Loading Body Voltage Test

Colour Fastness To Light Colour Fastness To Shampoo Sound Absorption Coefficient

Reduction in Impact Noise

Reduction in Impact Noise at 1000Hz

3230 Classic Fibre Bonded

85% Polypropylene 15% Nylon

30m 2m

915g/m² +/-10% 4.8mm +/-10% Heavy Contract Euroclass Cfl-s1

Tog Rating 0.89; ISO 8302: 0.09 m²K/W BS EN 985 Pass - suitable for continuous use BS 4939:1987 (2003) Recovery >80% (24hrs)

BS ISO 2094:1999 (2005) Loss <20% (1000 impacts)

BS ISO 6356:2000 <2kV

BS EN ISO 105 - B02 Minimum grade 6 BS 1006:UK-TB: 1990 Minimum Grade 4

BS EN 354:2003

BS EN ISO 140-8: Part 8: 1998 17dB BS EN ISO 140-8: Part 8: 1998 16.4dB

























This floor covering was made with renewable electricity



Environmental Profiles Scheme Certificate Number ENP353



Certificate Number FM01440 BS EN ISO 9001:2008



Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling – on a scale from A+ (very low-emission) to C (high-emission)

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications For specific rating, please refer to www.breeam.co.uk
- Burmatex products qualify for SKA as they achieve one or more requested criteria
- · All Burmatex carpet/carpet tile ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- · All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN United Kingdom T +44 (0) 1924 262 525 F +44 (0) 1924 280 033 UK email: projects@burmatex.co.uk International email: international@burmatex.co.uk www.burmatex.co.uk Burmatex reserves the right to improve the specification of all products without prior notification. E&OE

Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex. co.uk and recognised trade standards.

Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

LRV values for **3230 classic**

Product code	Product colour name	CIE Y	CIE L
2101	cornwall blue	4.47	25.18
2102	devon blue	6.50	30.65
2104	hampshire slate	7.54	33.02
2105	sussex sea	5.98	29.36
2106	kent mauve	9.29	36.53
2107	surrey blue	12.21	41.55
2109	glamorgan grey	3.81	23.02
2110	berkshire black	3.37	21.47
2111	wiltshire charcoal	6.68	31.06
2112	suffolk heather	6.20	29.91
2114	shropshire maroon	4.87	26.38
2115	norfolk sun	4.46	25.15
2117	cheshire jade	7.99	33.97
2118	yorkshire fern	9.48	36.89
2119	lancashire green	4.49	25.23
2126	grampian gold	5.56	28.27
2128	angus tan	10.77	39.20
2129	falkirk fawn	10.42	38.58