


technical specifications

Product Name	Zip
Product Description	Structure Bonded®
Pile Yarn Description	85% Polypropylene 15% Nylon
Tile Dimensions	50 cm x 50 cm
Pile Weight	1000g/m ² +/-10%
Total Weight	4250g/m ² +/-10%
Total Thickness	8.0mm +/-10%
Backing Description	Accummen™, 75% recycled
Wear Classification	Heavy Contract
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating 0.62; ISO 8302: 0.07 m ² K/W
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Static Loading	BS 4939: 1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN ISO 140-8: Part 8: 1998 17dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 140-8: Part 8: 1998 16.1dB
Number Of Tiles Per Box	20 (5m ²)


For best results we recommend*



Quarter Turn



Random



Brick

*All tiles within this design are unique and any linear aspects may not match from one tile to the next



This floor covering was made with renewable electricity



Environmental Profiles Scheme
Certificate Number ENP353



Certificate Number FM01440
BS EN ISO 9001:2008



Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A+ (very low-emission) to C (high-emission)

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications
For specific rating, please refer to www.breeam.co.uk
- Burmatex products qualify for SKA as they achieve one or more requested criteria
- All Burmatex carpet/carpet tile ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd
Victoria Mills, The Green
Ossett, West Yorkshire
WF5 OAN
United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE
Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards.
Orders are subject to Burmatex terms and conditions of sale.
See: www.burmatex.co.uk

LRV values for zip

Product code	Product colour name	CIE Y	CIE L
12801	sunset strip	5.83	28.97
12802	lime light	5.55	28.26
12804	scarlet ribbon	3.16	20.68
12806	steel cable	5.02	26.79
12812	quartz layer	6.32	30.20
12816	pink gin	3.30	21.22
12818	gold finger	6.37	30.33
12820	purple patch	2.90	19.64
12822	turquoise gem	5.13	27.10
12823	ink bar	3.74	22.79
12824	lavender star	4.10	23.99
12825	emerald queen	3.54	22.08
12826	pewter cast	6.84	31.44
12827	blue bay	3.00	20.04
12828	suede ribbon	2.44	17.66
12829	black tar	1.70	13.84
12830	diamond bolt	5.66	28.54
12831	indigo run	2.22	16.58